



Document Cameras

PV 360



PV 380



Sensor	1/3" CMOS, 2 Megapixel	1/3" CMOS, 2 Megapixel
Native Output Format	XGA (1024x768)	SXGA (1280x1024)
Effective Pixel	0.85 Megapixel	1.32 Megapixel
Converted Output Format	--	XGA
Resolution (Horizontal)	≥ 650 TV lines	≥ 750 TV lines
Zoom	24 (3x optical, 8x digital)	96 (8x optical, 12x digital)
Frame Rate (fps)	15	15
Shooting Area	Max: 12" x 10" / Min: 1/8" x 1/10"	Max: 12" x 10" / Min: 1/8" x 1/10"
Focus	Auto / Manual	Auto / Manual
White Balance	Auto / Manual	Auto / Manual
Color Adjustment	Yes	Yes
Brightness Adjustment	Yes	Yes
Image Split	Yes	Yes
Image Freeze	Yes	Yes
Image Mirror	Yes	Yes
Image Rotation	180°	--
Picture-in-Picture	--	Yes
BW/Color Conversion	Yes	Yes
Posi/Nega Conversion	Yes	Yes
Image Capture to Internal Memory	12 images (volatile)	12 images (volatile)
Image Capture to Computer	Yes	Yes
Video Recording to Computer	Yes	Yes
On-Screen Menu	Yes	Yes
INPUT PORTS		
VGA	--	x1
AUDIO	--	x1
OUTPUT PORTS		
VGA	x1	x1
C-VIDEO	--	x1
S-VIDEO	--	x1
AUDIO	--	x1
OTHER PORTS		
USB (slave, type B)	Capture/download images and videos to computer	Capture/download images and videos to computer
OTHER FEATURES		
Image/Video Capture Software	Window 2000, XP, Vista, 7 Mac OS10.4 or above.	Window 2000, XP, Vista, 7 Mac OS10.4 or above.
Remote Control	Yes(360°controllable)	Yes(360°controllable)
Kensington Lock Slot	Yes	Yes
Light Source	Embedded LED Lamp on Arm	Embedded LED Lamp on Arm
Operating Temperature	32°F to 104°F	32°F to 104°F
Dimensions	Folded: 12.6" x 6.6" x 3.7" Setup: 19.7" x 6.6" x 19.3"	Folded: 12.6" x 6.6" x 3.7" Setup: 19.7" x 6.6" x 19.3"
Power Supply	12V DC power adapter	12V DC power adapter
Weight (net)	5.5 lbs / 2.5 kg	5.5 lbs / 2.5 kg



WANIN USA

WANIN USA INC.

12961 Ramona Blvd., Suite H
Irwindale, CA 91706
URL: <http://www.waninusa.com>

Phone: 877-369-3130
Fax: 626-609-3380
Email: Sales@waninusa.com