

vidifox Document Cameras

DV 480



DV 550S



DV 550ST



Sensor	1/3" CMOS, 2 Megapixel	1/3" CMOS, 2 Megapixel	1/3" CMOS, 2 Megapixel
Native Output Format	SXGA (1280x1024)	SXGA (1280x1024)	XGA (1024x768)
Effective Pixel	1.32 Megapixel	1.32 Megapixel	0.85 Megapixel
Converted Output Format	XGA	XGA	--
Resolution (Horizontal)	≥ 750 TV lines	≥ 750 TV lines	≥ 750 TV lines
Zoom	96 (8x optical, 12x digital)	96 (8x optical, 12x digital)	96 (8x optical, 12x digital)
Frame Rate (fps)	15	15	15
Shooting Area	Max: 13" x 10" / Min: 1/8" x 1/10"	Max: 13" x 10" / Min: 1/8" x 1/10"	Max: 13" x 10" / Min: 1/8" x 1/10"
Focus	Auto / Manual	Auto / Manual	Auto / Manual
White Balance	Auto / Manual	Auto / Manual	Auto / Manual
Color Adjustment	Yes	Yes	Yes
Brightness Adjustment	Yes	Yes	Yes
Image Split	Yes	Yes	Yes
Image Freeze	Yes	Yes	Yes
Title Freeze	--	Yes	Yes
Image Mirror	Yes	Yes	Yes
Image Rotation	180°	90°, 180°, 270° (frozen)	90°, 180°, 270° (frozen)
Picture-in-Picture	--	Yes	Yes
Text Mode	--	Yes	Yes
BW/Color Conversion	Yes	Yes	Yes
Posi/Nega Conversion	Yes	Yes	Yes
Built-in Video Scalar	Yes	Yes	Yes
On-Screen Menu	Yes	Yes	Yes
Image Capture to Internal Memory	12 images (volatile)	400 images (non-volatile)	400 images (non-volatile)
to External USB Storage	--	Yes	Yes
to Computer	Yes	Yes	Yes
Video Recording to Computer	Yes	Yes, with sound	Yes, with sound
INPUT PORTS			
VGA	x2	x2	x2
C-VIDEO	x1	x1	x1
S-VIDEO	x1	x1	x1
AUDIO	x4	x4	x4
MICROPHONE	x1	x1	x1
OUTPUT PORTS			
DVI-A	--	x1	x1
VGA	x2	x2	x2
C-VIDEO	x1	x1	x1
S-VIDEO	x1	x1	x1
AUDIO	x1	x1	x1
OTHER PORTS			
USB (slave, type B)	Capture images and videos to computer	Capture/download images and videos to computer	Capture/download images and videos to computer
USB (host, type A)	--	For USB mouse or storage	For USB mouse or storage
RS232	x1	x1	x1
OTHER FEATURES			
Image/Video Capture Software	Window 2000, XP, Vista, 7 Mac OS10.4 or above.	Window 2000, XP, Vista, 7 Mac OS10.4 or above.	Window 2000, XP, Vista, 7 Mac OS10.4 or above.
Remote Control	Yes (360°controllable)	Yes (360°controllable)	Yes (360°controllable)
Kensington Lock Slot	--	Yes	Yes
Built-in LCD Screen	--	Yes	Touch Screen
Light Source	Arm Light x2 (LED) 10" x 8" Light Box (LED)	Top Arm Light x1 (LED) 10" x 8" Light Box (LED)	Top Arm Light x1 (LED) 10" x 8" Light Box (LED)
Operating Temperature	32°F to 104°F	32°F to 104°F	32°F to 104°F
Dimensions	Folded: 15.9" x 16.7" x 6.1" Setup: 18.7" x 16.7" x 22.3"	Folded: 19.48" x 14.56" x 5" Setup: 21.25" x 14.56" x 21.25"	Folded: 19.48" x 14.56" x 5" Setup: 21.25" x 14.56" x 21.25"
Power Supply	12V DC power adapter	12V DC power adapter	12V DC power adapter
Weight (net)	11 lbs / 5 Kg	11 lbs / 5 Kg	11 lbs / 5 Kg



WANIN USA

WANIN USA INC.

12961 Ramona Blvd., Suite H
Irwindale, CA 91706
URL: <http://www.waninusa.com>

Phone: 877-369-3130

Fax: 626-609-3380

Email: Sales@waninusa.com